

ENSTO

PRODUCT SPECIFICATION

14.08.2017



6418677639166


ECO16TOUCH
Combination thermostat

Code	ECO16TOUCH
GTIN	6418677639166
Name	Combination thermostat Combination thermostat
Description	A combination thermostat with touch screen for temperature control applying to one room at a time. Nominal current 16 A res. Maximum load 3600 W. Control 230 V. Voltage 230 V + 10 %, -15 %, 50 Hz. Control range +5°C...+40°C, Temperature restriction Min/Max. +5°C...+60°C. Week clock. Operating temperature 0°C...+30°C. 2-pole switch. Protection class IP21. NTC sensor 4 m, max diameter 7,5 mm, possible to extend to 10 m with MMJ 2 x 1,5 mm ² , 47 kΩ resistance in 25°C 47 kΩ. This thermostat is EcoDesign ready.
Vendor	Ensto Finland Oy


Technical specification
Dimensions

Weight: 0.2 kg

Ratings

Rated voltage: 230 V

Degree of protection: IP21

Rated frequency: 50Hz

Power: 3600 W

Rated current: 16 A

ETIM class: EC000298

ETIM
ETIM

Colour:	White
Max. switching current (resistive load):	16 A
Model:	Digital
Nominal voltage:	230 V
Differential gap:	0.4 K
Sensor element:	Electronic
Temperature:	5 ... 40 °C
Current supply:	Battery/mains
Time programs:	Day
Summer/Winter switch:	true

Packaging

Default package

Unit:	PCS
Size:	1
Length:	122 mm
Width:	104 mm
Height:	64 mm
Weight (brt):	0.31 kg
Volume:	0.81

Pallet package

Unit:	PCS
Size:	540
Length:	1200 mm
Width:	800 mm
Height:	1000 mm
Weight (brt):	204 kg
Volume:	1056